

SAFETY FIRST:

If you are collecting the equipment for someone else please make sure this sheet is given to the equipment user to read. In accordance with Health and Safety in Employment Act requirements, this sheet should be given to the site supervisor if the equipment is being hired for use at a commercial worksite so that the information is available to all users.

Required Safety Equipment



Ear Muffs



Hard Hat



Boots



Protective Clothing



Visual Inspection



Pre-Start Checks and Safety

- ! Fuel tank is full (diesel)
- ! Correct oil levels / engine and hydraulics
- ! Correct water level
- ! Check grease points lubricated
- ! Check for hydraulic and engine oil leaks
- ! Operate on even and level ground only
- ! Check the worksite before commencing work for underground services
- ! Ensure the machine is sized for the job
- ! Keep machine level when operating
- ! Do not allow inexperienced people to operate machine
- ! Keep people away from worksite
- ! Check cutting edges and ripper teeth
- ! Do not leave engine running or with blade in the air when unattended or out of driver's seat
- ! Do not allow people to ride on machine
- ! Ensure you have a minimum of 4 metres clearance when operating close to overhead wires
- ! Keep clear of beams, branches and other people on site etc
- ! Take extreme care on slippery surfaces and when loading and unloading unit onto trailers or trucks
- ! Do not use in confined areas

When Operating

NOTE: This sheet covers most models we have although some will differ slightly

- Do not operate this machine on uneven or unstable ground
- The dozer blade is always facing the front of the machine when going downhill
- Adjust and fasten the seat belt
- Raise control lever lock/s when mounting and dismounting the machine
- Familiarize yourself with the operations of the levers
- Ensure rippers are raised before moving machine

Starting procedure

- Move throttle lever to 1/3 throttle
- Cold start / turn key to glow position and hold for 10 seconds
- Start engine (NOTE: some models require the control lever lock arm to be raised to start engine)
- Check warning lamps are out and all gauges are within their operating range
- Return throttle lever to idle position and let engine warm up for 5 minutes

Stopping and After Use

- Park machine in a safe place
- Lower blade and rippers onto the ground
- Raise control lever lock/s
- Move throttle lever to idle position and allow engine to cool down for 3 minutes
- Move throttle lever to the stop position
- Turn off ignition